



FlutLED Ex 150W

Explosion-proof LED floodlight

Zone, 1, 21, 2 and 22



IP66



The FlutLED Ex 150W is suitable for all areas that require an efficient and extremely robust ex-lamp.

With its excellent light power this Explosion-proof LED floodlight is suitable for oil refineries, power and chemicals plants, offshore oil platforms, fire fighting, civil protection as well as stadium lighting.


Features

- strong light output
- shock and vibration resistant
- robust aluminum housing with anticorrosive paint
- tempered glass windscreen
- optimum luminous intensity distribution for different applications
- Through-wiring possible

Technical Data

Designation:	II 2G Ex db IIC T4/T5 Gb II 2D Ex tb IIIC T115°C/105°C/T95°C Db
Protection category:	IP66
Ex-Zone:	1, 2, 21 and 22
Output:	150W
Voltage:	100-277VAC
Overvoltage protection:	5kV
Frequency:	50/60Hz
Luminous flux:	22'050lm
Light output:	140lm/W
Light colours:	5'000K
Temperature range:	-40°C to +55°C
Lifetime:	>50'000h
Dimensions:	Ø330×197mm
Weight:	11kg

Dimensions



Item no.	Description
✓ 230130	FlutLED Ex 150W/230VAC 120° 5'000K IP66
<i>Pivotable mount 230131 is a mandatory accessory for 230130</i>	

Accessories	
✓ 230131	Stanchion mount to FlutLED Ex 150W
✓ 230132	Mounting ring M12 to FlutLED Ex 150W
✓ 230133	Pole mount bracket (without stirrup) to FlutLED Ex 150W

✓ from stock, offer subject to prior sale