





BetaLUXX



The LED ceiling light BetaLUXX is extremely robust with a high protection class of IP66. Because of the satinised glass the glare can be minimised but still guaranteeing an equal light distribution. The supplied mounting clips simplify installation. Because of this characteristics the BetaLUXX is versatile for utilisation in the industry and other fields harsh environments.

Technical Data

Voltage: 198 - 264 VAC (176 - 264 VDC)
 LED power: 20 W / 35 W / 55 W
 Luminous flux: 1'964 lm / 3'929 lm / 6'574 lm
 Light efficiency LED: 98.2 lm/W / 112 lm/W / 120 lm/W
 CRI-Index: Ra > 80
 Operating life LED: L70/B10 > 50'000 h
 Protection category: IP66
 Impact resistance: IK10
 Protection class: II
 Operating range of temperature: -25°C to +40°C
 Colour temperature: 3'000 K / 4'000 K / 5'000 K
 Beam angles: 120°
 Material housing: Aluminium
 Housing colour: grey
 Cover: polycarbonate
 UV resistance, halogen-free

Weight:
 - 20: 1'190 g
 - 40: 2'024 g
 - 60: 2'857 g

Dimensions H×L×W:
 - 20: 570×69.3×59.6 mm
 - 40: 1'046×69.3×59.6 mm
 - 60: 1'524×69.3×59.6 mm

Input voltage: Connection cable
 (not included with the lighting fixture)


BetaLUXX complete with plug and connector

	3'000 K	4'000 K	5'000 K	Designation
✓	860627	✓ 860626	✓ 860616	BetaLUXX 20 230 VAC, 1'964 lm
✓	860628	✓ 860614	✓ 860470	BetaLUXX 40 230 VAC, 3'929 lm
✓	860629	✓ 860615	✓ 860480	BetaLUXX 60 230 VAC, 6'574 lm
			✓ 860645	BetaLUXX 40, 230 VAC, 3'929 lm for food industry

Features

- high efficiency and uniformity of illuminance
- robust
- power-saving (low power/energy consumption with high light power)
- easy mounting with mounting clip (included in delivery)
- stainless spring steel (1.4301) mounting bracket
- pluggable
- with feed-through wiring

Dimensions



Accessories/spare parts	
✓	185329 BetaLUXX extension cable 2×1.5 mm ² , L=2.5m, incl. plug and connector
✓	188951 BetaLUXX extension cable 2×1.5 mm ² , L=3m, incl. plug and connector
✓	188952 BetaLUXX extension cable 2×1.5 mm ² , L=5m, incl. plug and connector
✓	187542 BetaLUXX connection cable 2×1.5 mm ² , L=5m, incl. plug T12 and connector
✓	860481 BetaLUXX connection cable 2.5 m 2×1.5 mm ² single-sided with connector
✓	860482 BetaLUXX connection cable 5 m 2×1.5 mm ² single-sided with connector
✓	183681 Plug 2P, 17.5A, 250 VAC, IP68, for cable Ø7-12 mm
✓	183680 Connector 2P, 17.5A, 250 VAC, IP68, for cable Ø7-12 mm
✓	036791 Cable H07RNF, 2×1.5 mm ² , black, Ø11 mm
✓	860632 BetaLUXX mounting bracket with screw locking for vertical mounting (2 piece per light)

✓ from stock, offer subject to prior sale