



Für einen entsprechenden normgerechten Unterbau, die fachgerechte Montage der Bodendose (max. Belastung 250kN) sowie entsprechende Drainagierung hat der Kunde zu sorgen.

Customer has to take care of professional foundation and mounting of underfloor distributor systems (max. load capacity 250kN) as well as professional connection to drainage system.

Fondation correspondante aux normes selon la charge admise (max. 250kN) et drainage nécessaire à faire par le client.

Per una corrispondente sottostruttura a norma, la corretta installazione del pozzetto (carico max. 250kN) come anche un drenaggio adeguato è a favore del cliente.

227016 KSV 7700 BG Campetto L  
181810 Poly 2525 BG Anschlussdose

A x B x C Aussparungsmasse  
Dim. of Recess  
Dim. maçonnerie  
Dimensioni d'incasso

**GIFAS**  
ELECTRIC

GIFAS-ELECTRIC GmbH  
Dietrichstrasse 2 - CH-9424 Rheineck  
☎ +41 71 886 44 44 ✉ info@gifas.ch  
📠 +41 71 886 44 44 🌐 www.gifas.ch

**Unterflurelektrant**  
**Campetto L C250 KSV 7700**

Art.-Nr. : **227026**

08.07.2024

Blatt 1/1  
beku