



Für einen entsprechenden normgerechten Unterbau, die fachgerechte Montage der Bodendose (max. Belastung 400kN) sowie entsprechende Drainagierung hat der Kunde zu sorgen.

Customer has to take care of professional foundation and mounting of underfloor distributor systems (max load capacity 400kN) as well as professional connection to drainage system.

Fondation correspondante aux normes selon la charge admise (max. 400kN) et drainage nécessaire à faire par le client.

Per una corrispondente sottostruttura a norma, la corretta installazione del pozzetto (carico max. 400kN) come anche un drenaggio adeguato è a favore del cliente.

256064 KSV 7800/2 BG Campetto XXL
251692 Poly 4025 BG Anschlussdose

A x B x C Aussparungsmasse Ausführung D400 gemäss Manual Campetto
Dim. of Recess Version D400 according to Campetto manual only
Dim. maçonnerie Exécution D400 selon manuel Campetto
Dimensioni d'incasso Esecuzione D400 come da manuale Campetto



GIFAS-ELECTRIC GmbH
Dietrichstrasse 2 - CH-9424 Rheineck
+41 71 886 44 44 info@gifas.ch
+41 71 886 44 44 www.gifas.ch

Unterflurelektrant
Campetto XXL D400 KSV 7800/2

Art.-Nr. : **256067**

19.11.2024

Blatt 1/1
beku